

Technical sheet :

WINCH



Technical characteristics

- Hydraulic motor with automatic cable end-of-travel limit switch.
- Oil-immersed negative braking system.
- Available in direct line pull or double line pull (model dependent).
- Certified swivel self-locking hook.
- Storage stand equipped with integrated fork sleeves for easy handling.
- Note: dimensions provided below refer to the winch when placed on its stands.

[The 3D picture at the top of this page is the reference Winch 5T - 921341].

Customer benefits

- Turns your telehandler into a crane.
- Extremely fast implementation on the MANITOU carriage.
- Fast and accurate movements.

		W 3T	W 3T	W 3T TD	W 5T	W 3000/36M
Reference number		885236	921337	939111	921341	52717650
Working height (mm)	h21	24000	24000	46000	24000	36000
Capacity (kg)		3000	3000	3000	5000	3000
Overall weight (kg)		310	385	480	495	398
Height (mm)		1810	1869	1869	1869	1803
Length (mm)		900	900	900	900	900
Max. outreach (mm)		519	515	689	541	515
Cable		1 loop	1 loop	Direct	1 loop	1 loop
Width (mm)		1080	1080	1080	1080	1080
Required machine equipment						
Hook Speed (m/mn)		15	15	30	14	27
E-RECO		Yes	Yes	Yes	Yes	Yes
Connection system		Manitou	Manitou	Manitou	Manitou	Manitou

Machines compatibility					
MRT 1845 75	-	X	X	X	-
MRT 1845 115	-	X	X	X	-
MRT 2145 115	-	X	X	X	-
MRT 2260	-	-	-	-	X
MRT 2260 e	-	-	-	-	X
MRT 2545 115	-	X	X	X	-
MRT 2570	-	-	-	-	X
MRT 2660	-	-	-	-	X
MRT 2660 e	-	-	-	-	X
MRT 3060	-	-	-	-	X
MRT 3570	-	-	-	-	X
MRT 3570 ES	-	-	-	-	X
MRT-X 1845	-	X	X	X	-
MRT-X 2145	-	X	X	X	-
MRT-X 2260	-	-	-	-	X
MRT-X 2545	-	X	X	X	-
MRT-X 2570	-	-	-	-	X
MRT-X 2660	-	-	-	-	X
MRT-X 3060	-	-	-	-	X
MRT-X 3570	-	-	-	-	X
MRT-X 3570 ES	-	-	-	-	X
MT 735 75D ST5	X	-	-	-	-
MT 935 75D ST5	X	-	-	-	-
MT 1135 75 D	X	-	-	-	-
MT 1135 H 100D	X	-	-	-	-
MT 1335 75D ST5	X	-	-	-	-
MT 1335 100D ST5	X	-	-	-	-
MT 1335 H 75D ST5	X	-	-	-	-
MT 1335 H 100D ST5	X	-	-	-	-
MT 1335 HA 75D ST5	X	-	-	-	-
MT 1335 HA 100D ST5	X	-	-	-	-
MT 1440 e	X	-	-	-	-
MT 1440 easy ST5	X	-	-	-	-
MT 1440 ST5	X	-	-	-	-
MT 1840 e	X	-	-	-	-
MT 1840 easy ST5	X	-	-	-	-
MT 1840 ST5	X	-	-	-	-
MT-X 735	X	-	-	-	-
MT-X 1135	X	-	-	-	-
MT-X 1440	X	-	-	-	-
MT-X 1840	X	-	-	-	-
MRT 1645 75 OLD	-	X	X	X	-
MRT 1645 115 OLD	-	X	X	X	-
MRT-X 1645 OLD	-	X	X	X	-
MT 1440 A ST5 OLD	X	-	-	-	-
MT 1440 HA ST5 OLD	X	-	-	-	-
MT 1840 A ST5 S1 OLD	X	-	-	-	-
MT 1840 HA ST5 S1 OLD	X	-	-	-	-
MT-X 1440 A OLD	X	-	-	-	-
MT-X 1840 A OLD	X	-	-	-	-

Reference number		W 3000/48M DI	W 3000/63M+ DI	W 6000/32M	W 6000/56M
		52717900	52854161	52717351	52813130
Working height (mm)	h21	48000	63000	32000	56000
Capacity (kg)		3000	3000	6000	6000
Overall weight (kg)		490	410	532	577
Height (mm)		1803	1803	1803	1779
Length (mm)		900	900	900	900
Max. outreach (mm)		689	-	542	550
Cable		Direct	Direct	1 loop	1 loop
Width (mm)		1080	1080	1080	1080
Required machine equipment					
Hook Speed (m/mn)		35	-	17	-
E-RECO		Yes	Yes	Yes	Yes
Connection system		Manitou	Manitou	Manitou	Manitou

Machines compatibility				
MRT 2145 115	-	-	X	-
MRT 2260	X	-	X	-
MRT 2260 e	X	-	X	-
MRT 2570	X	-	X	-
MRT 2660	X	-	X	-
MRT 2660 e	X	-	X	-
MRT 3060	X	-	X	-
MRT 3570	X	-	X	-
MRT 3570 ES	X	-	X	-
MRT 4080	-	X	-	X
MRT-X 2260	X	-	X	-
MRT-X 2570	X	-	X	-
MRT-X 2660	X	-	X	-
MRT-X 3060	X	-	X	-
MRT-X 3570	X	-	X	-
MRT-X 3570 ES	X	-	X	-
MRT-X 4080	-	X	-	X

TABLE SYMBOL					
	No predisposition required		Hydraulic line		Return piping to hydraulic oil tank
	Electric predisposition		Platform predisposition		Tyre handler, cylinder handler predisposition



Head Office

B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes